


HIGH PERFORMANCE PAINTING MASKING TAPE

C-586G | Green



DESCRIPTION

Unleash precision and speed with our Cellux High Performance Paint Masking Tape C-586G. This tape is carefully designed to achieve crisp paint lines and efficient masking during high-performance automotive projects. With superior adhesion and durability, it ensures a seamless application, whether you're customizing, detailing, or conducting racing-inspired paint jobs.

USES

- ✓ Water and solvent-based painting projects.
- ✓ High-temperature applications.
- ✓ Bodywork and repairs.
- ✓ Auto-detailing.
- ✓ Excellent performance on curves profiles.
- ✓ Crisp paint lines.

FEATURES

- ✓ Design to resist moisture.
- ✓ IR lamps and spray booth.
- ✓ 194°F x 30 min / 248°F x 1 hour.
- ✓ High performance and visibility.
- ✓ Uv resistant .
- ✓ 10 days outdoor use.

TECHNICAL DATA

Property	Standard
Backing	Advanced semi-crepe
Adhesive	Natural Rubber-based
Adhesion to Steel	31.7 (oz/in)
Indoor/Outdoor	Indoor - Outdoor
Service temperature	248°F (1 Hour) - 194°F (30 Min)

STORAGE CONDITIONS

Tape storage guidelines recommend keeping it in its original packaging, ensuring a cool and dry environment, away from direct sunlight. It is advisable to utilize the tape within 12 months from the date of shipment. Moreover, when applying the tape, ensure that the surfaces are clean, dry, and devoid of any grease, oil, or other contaminants.

HOW TO USE

- 1 Clean the surface.
- 2 Unroll, cut and apply.
- 3 Apply pressure with your hand reinforcing the adhesion.

SIZE

Widths (in) Lengths (yd)

Widths (in)	Lengths (yd)
3/4"	60
1"	
1 1/2"	
2"	

All measurements are available in individual rolls.

At Cellux we understand that each project is different. We can manufacture the size according to your requirement.



"INNOVATIVE ADHESIVE TAPE SOLUTIONS FOR EVERY INDUSTRY."

