

# PRODUCT CATALOG

[www.cellux.com](http://www.cellux.com)

Cellux <sup>+</sup>





**1882**  
FOUNDING



**1914**  
FOUNDING



**1882**  
FOUNDING

With over 140 years in the adhesive tape industry, and a strong presence in several countries around the world, Cellux has arrived in the United States to offer excellent quality adhesive tapes at the most competitive prices.

We understand our customer needs: when we talk about adhesive tape, we talk about effectiveness, unobtrusiveness when adding unobtrusively. We seek to meet each person by offering just what they need in the most accessible way.

Optimize your operation with Cellux and find any tape solution with our high-quality line of products: from packaging and masking tapes to refrigeration tapes and more.

## CONTENTS

### MAKING SOLUTIONS

- General purpose masking tape
- Customer made masking tape
- Heavy duty masking tape
- Blue bottom's masking tape
- Marine performance fabric Masking tape
- Automotive performance fabric Masking tape

### SURFACE PROTECTION SOLUTIONS

- Seal bottom tape
- Blue insulation film - window board

### PACKAGING SOLUTIONS

- Heavy duty masking tape
- Automotive tape
- Masking film
- Heavy board

### SPECIALTY PACKAGING SOLUTIONS

- Reinforced masking tape
- Reinforced bottom tape

### REFRIGERATION SOLUTIONS

- Seal tape
- Reinforced aluminum foil tape that
- aluminum foil tape

### FOAM TAPE

- Insulation/insulation tape
- Insulation/insulation tape

### ELECTRICAL SOLUTIONS

- Industrial electrical tape

**Cellux**   
CORPORATION

# MASKING SOLUTIONS

INNOVATIVE ADHESIVE  
TAPE SOLUTIONS FOR  
EVERY INDUSTRY.™



 [www.cellux.com](http://www.cellux.com)

# GENERAL PURPOSE MASKING TAPE

C-364



Our General Purpose Masking Tape is a reinforced adhesive film with a range of applications suitable for temporary masking and easy removal. The masking film quickly and easily peels away from surfaces leaving no residue remaining on the surface of your workpiece. The tape allows strong, accurate and consistent lines of seal forming a barrier which prevents unwanted paint or staining from reaching the surface.

See additional use information on General Purpose Masking Tape in the application section of your masking needs.

- 1. Temporary application
- 2. Excellent adhesion
- 3. Easy to remove
- 4. Temporary protection

ITEM	WIDTH (mm)	LENGTH (m)	REEL WEIGHT (kg)	ROLLS
C-364-000001	19"	30	18	18
C-364-000002	19"	30	18	18
C-364-000003	1"	30	18	18
C-364-000004	1 1/2"	30	18	18
C-364-000005	1"	30	18	18
C-364-000006	1"	30	18	18

# CONTRACTOR GRADE MASKING TAPE

C-366



Our black Contractor Grade Masking Tape is a reinforced paper tape specially designed for high performance surface protection and labelling in the construction, industrial and marine industries. It is ideal for use indoors or in high outdoor environments where wind, water, plants and other aggressive forces without any damage and.

- 1. High adhesion
- 2. Excellent weathering
- 3. Multi surface
- 4. Environmentally sustainable and recyclable

ITEM	WIDTH (mm)	LENGTH (m)	REEL WEIGHT (kg)	ROLLS
C-366-000001	19"	30	18	18
C-366-000002	19"	30	18	18
C-366-000003	1"	30	18	18
C-366-000004	1 1/2"	30	18	18
C-366-000005	1"	30	18	18



## BODY SHOP

ALUMINUM TAPES

C-888



Devcon Body Shop Aluminum Tape is made from two steps processes: a special primer film. The tape bonds top performance qualities such as resistance, adhesion, and water resistance. Also, its unique outer surface features superior abrasion and stability, making it ideal for use with heated repair tape temperatures up to 50 degrees for protection of cracks caused by engine failures and water damage with cooling fans and air ducts. Its adhesive is fully cured in 15 minutes and is available in a variety of colors for use in 15 degree Celsius settings.

- Superior strength
- 15 degree Celsius
- Excellent performance
- High performance stability

SIZE	WIDTH (IN)	LENGTH (FT)	QUANTITY	PRICE
DEVCON BODY SHOP	1 1/2"	50'	10	\$
DEVCON BODY SHOP	2"		10	\$
DEVCON BODY SHOP	1 1/2"		10	\$
DEVCON BODY SHOP	2"		10	\$

## BLUE PAINTER'S

ALUMINUM TAPE

C-876



Blue Painter's Aluminum Tape is made from two steps processes: a special primer film. The tape bonds top performance qualities such as resistance, adhesion, and water resistance. Also, its unique outer surface features superior abrasion and stability, making it ideal for use with heated repair tape temperatures up to 50 degrees for protection of cracks caused by engine failures and water damage with cooling fans and air ducts. Its adhesive is fully cured in 15 minutes and is available in a variety of colors for use in 15 degree Celsius settings.

- Superior strength
- 15 degree Celsius
- Excellent performance
- High performance stability

SIZE	WIDTH (IN)	LENGTH (FT)	QUANTITY	PRICE
DEVCON BLUE PAINTER'S	1 1/2"	50'	10	\$
DEVCON BLUE PAINTER'S	2"		10	\$
DEVCON BLUE PAINTER'S	1 1/2"		10	\$
DEVCON BLUE PAINTER'S	2"		10	\$

# WATERPROOF

## MASTIC TAPET

### C-888C



Durox **WATERPROOF Mastic Tapet** is a specialized solution for protection and efficient maintenance of your projects. Thanks to its water-repellent structure,

it has excellent adhesion. The tape is made of elastic glass with 10-year durability and is resistant to UV exposure, performance that allows for continuous exterior protection. This innovative structure is designed to reduce the signs of deterioration in concrete.

- Sustainable price
- Sustainable B2B solution
- Waterproof and UV resistant
- 10-year water-repellent structure maintenance

TYPE	WIDTH (CM)	LENGTH (CM)	WEIGHT (KG)	ROLLS
1. WATERPROOF MASTIC TAPET	10	100	10	10
2. WATERPROOF MASTIC TAPET	15		10	10
3. WATERPROOF MASTIC TAPET	20		10	10

# WATERPROOF

## SUPERIOR

### MASTIC TAPET

### C-888C



Durox **WATERPROOF Superior Mastic Tapet** is the perfect solution for your roofing needs. It features excellent adhesion, makes your exterior

space safe, and offers an excellent appearance. It is designed to last longer than the average. Thanks to its superior performance in wet conditions and with reinforced joints, it is ideal for exterior exterior concrete high adhesion and ability, making it perfect for your exterior concrete.

and long-term. The Durox waterproofing system is suitable for external. It is up to 10 days in external settings. That makes the waterproofing process an easy project.

- Sustainable B2B solution
- Superior Waterproof and UV resistant
- 10-year water-repellent structure maintenance
- Superior painting and roofing applications

TYPE	WIDTH (CM)	LENGTH (CM)	WEIGHT (KG)	ROLLS
1. WATERPROOF SUPERIOR MASTIC TAPET	10	100	10	10
2. WATERPROOF SUPERIOR MASTIC TAPET	15		10	10
3. WATERPROOF SUPERIOR MASTIC TAPET	20		10	10

# SURFACE PROTECTION SOLUTIONS

INNOVATIVE ADHESIVE  
TAPE SOLUTIONS FOR  
EVERY INDUSTRY.



Cellux  
INDUSTRIAL

# RED STUCCO

TAPE  
C-792



The Red Stucco Tape (RST) is an essential tool for construction projects such as installing corners, chimney, and structures. When working on these tasks, having a high-quality stucco tape makes a big difference in efficiency and durability of the construction project. For successful corners to complete their projects.

- Superior strength
- High durability, making it suitable for demanding applications.
- Resistant to UV and moisture.

Code	Thickness (mm)	Width (cm)	Length (m)	Weight (kg)	Dimensions (mm)
1 - 00000000000000000000	2,0	27	50	24	1000x1000



# WINDOW GUARD

ULTRAVIOLET PROTECTION FILM  
C-330



The blue protection film for windows (WLF) is made of polyethylene film. This product allows to prevent fading from edges to edge, allowing the film to stay in place, although it has the necessary adhesion to get the job done. It can be removed up to 90 days with clean solvent, without damaging the window or the glass panes. It is suitable for both interior and exterior environments.

- Excellent performance during construction projects.
- Self-adhesive polyethylene film.
- Blue color.
- 90 days clean removal.
- Suitable for outdoor use.

Code	Thickness (mm)	Width (cm)	Length (m)	Weight (kg)	Dimensions (mm)
1 - 00000000000000000000	1,00	27	50	7	1000x1000



Cellux   
AMERICA'S

# PACKAGING SOLUTIONS

“INNOVATIVE ADHESIVE  
TAPE SOLUTIONS FOR  
EVERY INDUSTRY.”



 [cellux.us](http://cellux.us)

# HEAVY DUTY PACKAGING TAPE

C-736/C-736



The Heavy Duty 1000PS packaging tape is ideal for packaging requiring superior performance. Its properties make this a highly weight-efficient tape designed for heavy-duty industrial sealing applications. Its heavy aggregate adhesive provides the necessary strength and support for the most demanding packaging work.

- Superior strength
- High durability, making it suitable for demanding applications.
- Resistant to oil and moisture.

Model	Thickness (mm)	Weight (g/m <sup>2</sup> )	Adhesive Type	Temperature	Temperature
C-736-0.015	0.015	120	PS	50	120°C
C-736-0.020		160		50	120°C
C-736-0.025		200		50	120°C
C-736-0.030		240		50	120°C

## C-736



The lowest grade of HD packaging tape supported by our best weight value. The ideal way for creating extra adhesive offers great strength and durability. Thanks to its 0.015 thickness, it is the most economical adhesive option. It is very useful for heavy-duty storage. The adhesive is resistant to oil and moisture, making it suitable for packaging in oil and water.

## C-735



The middle grade of HD packaging tape is the ideal for the packaging industry where greater resistance is required. It offers an 18-20% weight increase. Thanks to its 0.020 thickness, the best resistance ratio is achieved, guaranteeing a long useful life during storage. The tape can be effectively waterproofed by packaging it with a plasticizer.

## C-738



The highest grade of HD packaging tape is the most ideal for the packaging industry where greater resistance is required, offering an 18-20% weight increase. Thanks to its 0.025 thickness, it provides the best resistance ratio. It is very useful for heavy-duty storage.



INDUSTRIAL PRODUCT



# SPECIALTY PACKAGING SOLUTIONS



"INNOVATIVE ADHESIVE  
TAPE SOLUTIONS FOR  
EVERY INDUSTRY"





# REFRIGERATION SOLUTIONS

"INNOVATIVE ADHESIVE  
TAPE SOLUTIONS FOR  
EVERY INDUSTRY"



# DUCT TAPE

C-386



## DUCT TAPE

Duct Tape (model C-386) is a adhesive tape that contains polypropylene cloth and polyethylene film with a strong rubber adhesive covering the cloth. Duct tape is used for many applications, it is used primarily for construction repairs. It can be used on irregular surfaces like construction, automotive and home repairs. One of the best features is that it's the only adhesive tape that can stick to wet surfaces.

- ✔ Aggressive adhesive
- ✔ Excellent cold temperature performance
- ✔ Exceptional bonding power for indoor and outdoor use
- ✔ Sticks immediately
- ✔ Removable with no residue

Model	Thickness (mm)	Width (mm)	Length (m)	Weight (kg)	Dimensions (mm)
C-386-300-10000	1.2	48	100	0.4	300x10000



# FOIL TAPE

## C-387



### FSE REINFORCED ALUMINUM FOIL TAPE

The reinforced aluminum foil tape (underlayment grade) **C-387** is a tape designed for superior performance thermal applications. Its fiberglass reinforcement makes it more resistant to the stretching, sagging and tearing of roofing systems. Its adhesive provides long service life in long-term applications.

- Strengthens surfaces used in reflective temperature sensitive
- Its fiberglass reinforcement makes it more resistant to stretching, sagging and tearing
- The material is impervious to water vapor and acids, providing superior protection and durability

ITEM	Thickness (mil)	Width (in)	Length (ft)	Weight (lb)	Application
C-387	4.5	2"	60'	2.4	Roof, shingle wrap
C-387		3"	60'	3.6	Roof, shingle wrap

### ALUMINUM FOIL TAPE

# FOIL TAPE

## C-384



The aluminum foil tape (underlayment grade) **C-384** is a high-quality adhesive tape designed for metal applications and general purposes use. Made from strong, non-stretching material, this tape is perfect for sealing ducts, vents, airways, as well as for insulation and other general roofing purposes. Its heat-resistant properties make it ideal for use in hot and cold environments, and its strong adhesive allows it to seal and insulate both horizontal and vertical surfaces. Perfect solution for metal professionals, contractors, and anyone who you will need a durable and durable tape for all their roofing and insulation needs.

- Heat resistant (up to 300°)
- Highly adhesive
- Aggressive strips the adhesive
- Heat resistant substance
- Waterproofing
- Bonds various materials to
- Seals other applications
- Effective in long-term use

ITEM	Thickness (mil)	Width (in)	Length (ft)	Weight (lb)	Application
C-384	3.5	2"	60'	2.1	Roof, shingle wrap
C-384		3"	60'	3.2	Roof, shingle wrap

**Cellux**   
EST. 1962

# FOAM TAPES

"INNOVATIVE ADHESIVE  
TAPE SOLUTIONS FOR  
EVERY INDUSTRY."



 [cellux.us](http://cellux.us)



# NEOPRENE TAPE

C-676



## DOUBLE SIDED NEOPRENE TAPE

The C-676 black neoprene foam tape is a special high-strength, double-sided tape designed for providing support on a variety of surfaces and environments. It is well suited to long duration applications for the automotive industry.

- High performance in environmental conditions.
- Great for stamping.
- Guarantees a safe mounting.
- High resistance.
- Enables application on multiple surfaces.
- Long duration.
- Resistant to industrial and automotive chemicals.
- Oil resistant.

Code	Thickness (mm)	Width (mm)	Length (m)	Structure	Dimensions
C-676	30	50	20	10	individual roll
C-676		7	20	10	individual roll
C-676		100	20	8	individual roll



For more information on our products, visit [www.dow.com](http://www.dow.com)



# POLYETHYLENE TAPE

## DOUBLE SIDED POLYETHYLENE TAPE



**D-488**

The double sided adhesive tape (D-488) is specially designed for join the wall panels lightweight objects in the structure and construction works. Besides the use of tapes and adhesives, it is used to repair objects such as concrete, light concrete, plaster etc.



**D-489**

The double-sided adhesive tape (D-489) is a permanently designed for the joints and assembly of lightweight objects in the structure and construction works. Besides the use of tapes and adhesives, it is used to repair objects such as concrete, light concrete, plaster etc.



**D-490**

The adhesive with base tape (D-490) is a fast drying designed for the joints and assembly of medium-weight objects, masonry, the concrete walls. It can be used to repair, plaster and along others. It is used in interior, exterior, swimming, construction, etc.

- Superior resistance to adhesion to a variety of surfaces, including non-adhesive strong materials.
- Resistant to moisture and other environmental factors.
- Excellent workability.
- Good resistance and temperature resistance.
- Excellent self-healing.
- Long service life and long life.

NO.	DESCRIPTION	WIDTH (mm)	LENGTH (m)	WEIGHT (kg)	APPLICATION
1	D-488	50	50	0,25	Interior and exterior
2		50	100	0,50	Interior and exterior
3		50	150	0,75	Interior and exterior
4		50	200	1,00	Interior and exterior
5		50	250	1,25	Interior and exterior
6		50	300	1,50	Interior and exterior

NO.	DESCRIPTION	WIDTH (mm)	LENGTH (m)	WEIGHT (kg)	APPLICATION
1	D-489	50	50	0,25	Interior and exterior
2		50	100	0,50	Interior and exterior
3		50	150	0,75	Interior and exterior
4		50	200	1,00	Interior and exterior
5		50	250	1,25	Interior and exterior
6		50	300	1,50	Interior and exterior

NO.	DESCRIPTION	WIDTH (mm)	LENGTH (m)	WEIGHT (kg)	APPLICATION
1	D-490	50	50	0,25	Interior and exterior
2		50	100	0,50	Interior and exterior
3		50	150	0,75	Interior and exterior
4		50	200	1,00	Interior and exterior
5		50	250	1,25	Interior and exterior
6		50	300	1,50	Interior and exterior

Cellux   
1987-2017

# ELECTRICAL SOLUTIONS

"INNOVATIVE ADHESIVE  
TAPE SOLUTIONS FOR  
EVERY INDUSTRY."



 [cellux.us](http://cellux.us)

# ELECTRICAL TAPE

C-878



## INDUSTRIAL ELECTRICAL TAPE

The C-878 Industrial electrical tape is a self-adhesive tape ideal for projects in the electricity industry. Certified under the IEC61010 standard, Cellux electrical tape has excellent elongation and memory recovery properties. The C-878 is designed and insulates up to 600V.

- Stretch and flexibility.
- Resistant to abrasion, moisture, alkalies, acids, corrosion, and varying weather conditions.
- Cold and sunlight resistant.

Part	Thickness (mm)	Width (mm)	Length (m)	Resistance	Application
C-878	3	32	6	100	Heat shrink wrap



Cellux is a registered trademark of Cellux S.p.A. All rights reserved. Cellux S.p.A. - Via S. Maria 10 - 20139 Milano - Italy



SAFE  
C-578  
34" x 60"  
100 lbs (45kg)

Cellux

defined  
edges.



ce

Cellux



Cellux +  
EST. 2018